



## Camlocks

### Working Pressure

SIZE RANGE (mm)	ALUMINIUM, STAINLESS, BRONZE, BRASS
15	1034kPa
20-50	1724kPa
65	1034kPa
75	862kPa
100	690kPa
125	517kPa
150	517kPa



### Specifications

Camlocks are also known as Cam and Groove Fittings

The AAP Industries range of Camlock are manufactured to interchange with all product produced to Mil Spec A-A 59326. Size 1/2" (15mm) and 8" (200mm) fittings are not covered by Mil Spec A-A 59326, these sizes are to manufactures specification only.

Used where quick, convenient connection and disconnection of piping and hose is required.

**Industries** – Irrigation, Pumping, Hose Distributors, Bulk Tankers, Water Carriers, General Industry.

**Medium** – Water, Oil, Powders, some Hydrocarbons and Chemicals (check compatibility charts).

**Threads** - The threads are cut according to ISO 228

**Maximum Temperature** – NBR (Buna) Gasket 100 degree Celcius.

**Spare Parts** – AAP have available a range of spare parts to suit the camlocks, such as Brass Handles (code CBH...), Handle Pins (code CP....), and NBR Gaskets (code CGN...).

#### PRODUCT SUMMARY

PRODUCT SUMMARY	
TYPE A	Male Camlock x Female BSP
TYPE B	Female Camlock x Male BSP
TYPE C	Female Camlock x Hosebarb
TYPE D	Female Camlock x Female BSP
TYPE E	Male Camlock x Hosebarb
TYPE F	Male Camlock x Male BSP
TYPE DC	Dust Cap
TYPE DP	Dust Plug

*Disclaimer: Information and photographs shown are for marketing purposes only. Actual product may vary to images shown due to continual improvement processes, design changes and optional extras*

#### AUSTRALIA

+61 3 9775 1366  
sales@fuelco.com.au  
FUELCO.COM.AU

#### AFRICA

+27 16 421 8043  
sales@fuelco-sa.com  
FUELCO-SA.COM

#### MENA

+ 971 4 232 6985  
sales@fuelco.ae  
FUELCO.AE

#### EUROPE/UK

+ 971 4 232 6985  
sales@fuelco.uk  
FUELCO.UK